



SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Name: DYNAGRIP EPOXY PASTE – 17002 HARDENER 28gm

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use: Adhesive

Details of Manufacturer or Importer:

AFC International Pty Ltd
21-23 Hobart Street
Riverstone NSW 2765

Phone Number: +61 2 9627 7125

Emergency telephone number: +61 2 9627 7125

2. HAZARDS IDENTIFICATION

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Signal Word Warning

Hazard Statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary Statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 2)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 HARDENER 28gm

P501

Dispose of contents/container in accordance with local/regional/national regulations. (Contd. of page 1)

3 . COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Characterization: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.

Hazardous Components:		
1317-65-3	Limestone ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	30 - 60%
7727-43-7	Sulfuric acid, barium salt (1:1)	10 - 30%
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	5 - 10%
546-93-0	Carbonic acid, magnesium salt (1:1)	1 - 5%
7631-86-9	Silica	1 - 5%

4 . FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, hold eyelids open and rinse with water for at least 15 minutes. Seek medical attention if symptoms occur.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Give a glass of water. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

5 . FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Use fire extinguishing methods suitable to surrounding conditions.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon, nitrogen and sulphur and metal oxides. Product does not sustain combustion.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 . ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved dust/particulate filter respirator and full protective clothing. Evacuate all non-essential personnel from affected area. Do not breathe dust. Ensure adequate ventilation. Avoid generating dust.

Environmental Precautions: In the event of a major spill, prevent spillage from entering drains or water courses.

(Contd. on page 3)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 HARDENER 28gm

(Contd. of page 2)

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so, collect with a HEPA vacuum or by sweeping and place in a suitable container for subsequent disposal. Avoid generating dust. Provide adequate ventilation.

7 . HANDLING AND STORAGE

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of dust. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep in original container tightly closed. Do not store above 35 °C.

8 . EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Standards:	
7727-43-7 Sulfuric acid, barium salt (1:1)	
NES	TWA: 10 mg/m ³
14807-96-6 Talc (Mg3H2(SiO3)4)	
NES	TWA: 2.5 mg/m ³
546-93-0 Carbonic acid, magnesium salt (1:1)	
NES	TWA: 10 mg/m ³
7631-86-9 Silica	
NES	TWA: 2 mg/m ³

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapour below occupational exposure standards.

Respiratory Protection:

Where an inhalation risk exists, wear a Class P1 (particulate) respirator. At high dust levels, wear a powered air purifying respirator (PAPR) with Class P3 (Particulate) filter or an air-line respirator or a full-face Class P3 (particulate) respirator. See Australian/New Zealand Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Chemical resistant, impervious gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against dust. See Australian/New Zealand Standard AS/NZS 1337 for more information.

(Contd. on page 4)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 HARDENER 28gm

(Contd. of page 3)

9 . PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	
Form:	Solid
Colour:	Black
Odour:	Pungent, sulphurous.
Odour Threshold:	No information available
pH-Value:	No information available
Melting point/Melting range:	No information available
Initial Boiling Point/Boiling Range:	No information available
Flash Point:	> 93.3 °C
Flammability:	Product does not sustain combustion.
Auto-ignition Temperature:	No information available
Decomposition Temperature:	No information available
Explosion Limits:	
Lower:	No information available
Upper:	No information available
Vapour Pressure:	Not applicable.
Relative Density:	1.753
Vapour Density:	No information available
Evaporation Rate:	No information available
Solubility in Water:	No information available
Partition Coefficient (n-octanol/water):	No information available

10 . STABILITY AND REACTIVITY

Possibility of Hazardous Reactions: No hazardous reactions will occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: No further relevant information available.

Incompatible Materials: No further relevant information available.

Hazardous Decomposition Products: Oxides of carbon, nitrogen and sulphur and metal oxides.

11 . TOXICOLOGICAL INFORMATION

Toxicity:

LD ₅₀ /LC ₅₀ Values Relevant for Classification:		
1317-65-3 Limestone		
Oral	LD ₅₀	6450 mg/kg (rat)
7631-86-9 Silica		
Oral	LD ₅₀	10000 mg/kg (rat)

Acute Health Effects

Inhalation: May cause respiratory irritation.

Skin: Causes skin irritation.

Eye: Causes serious eye irritation.

Ingestion: No information available

(Contd. on page 5)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 HARDENER 28gm

(Contd. of page 4)

Skin Corrosion / Irritation: Causes skin irritation.**Serious Eye Damage / Irritation:** Causes serious eye irritation.**Respiratory or Skin Sensitisation:** Based on classification principles, the classification criteria are not met.**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.**Carcinogenicity:**

Silica, amorphous and talc not containing asbestos or asbestiform fibres are classified by IARC as Group 3 - Not classifiable as to its carcinogenicity to humans.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.**Specific Target Organ Toxicity (STOT) - Single Exposure:** May cause respiratory irritation.**Specific Target Organ Toxicity (STOT) - Repeated Exposure:**

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.**Chronic Health Effects:**

The prolonged and repeated exposure (by inhalation) to respirable (crystalline) silica cause silicosis, a debilitating lung disease. The crystalline silica dust is practically insoluble in body fluids and can be deposited in lungs. Cigarette smoking can reduce the clearance of crystalline silica. The data indicate that the relative lung cancer risk is increased for people with silicosis.

Repeated or prolonged exposure may cause damage to the lungs, upper respiratory tract, skin and eyes.

Existing Conditions Aggravated by Exposure: No information available

12 . ECOLOGICAL INFORMATION

Ecotoxicity:

Aquatic toxicity:	
7727-43-7 Sulfuric acid, barium salt (1:1)	
EC ₅₀ /48 h	634 mg/L (crustacea)
7631-86-9 Silica	
EC ₅₀ /72 h	55.5 mg/L (algae)

Persistence and Degradability: No information available**Bioaccumulative Potential:** No information available**Mobility in Soil:** No information available**Other adverse effects:** No information available

13 . DISPOSAL CONSIDERATIONS

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

(Contd. on page 6)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 HARDENER 28gm

(Contd. of page 5)

14 . TRANSPORT INFORMATION

UN Number Not regulated
 Proper Shipping Name Not regulated
 Dangerous Goods Class Not regulated
 Packing Group: Not regulated

15 . REGULATORY INFORMATION

Australian Inventory of Chemical Substances:

1317-65-3	Limestone
7727-43-7	Sulfuric acid, barium salt (1:1)
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)
546-93-0	Carbonic acid, magnesium salt (1:1)
7631-86-9	Silica

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule: Not Scheduled.

16 . OTHER INFORMATION

Date of Preparation or Last Revision: 25.01.2021

Prepared by: MSDS.COM.AU Pty Ltd

www.msds.com.au

Abbreviations and acronyms:

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC₅₀: Lethal concentration, 50 percent

LD₅₀: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Disclaimer

This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - December 2011"

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. AFC International Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.



SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Name: DYNAGRIP EPOXY PASTE – 17002 RESIN 28gm

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use: Adhesive

Details of Manufacturer or Importer:

AFC International Pty Ltd
21-23 Hobart Street
Riverstone NSW 2765

Phone Number: +61 2 9627 7125

Emergency telephone number: +61 2 9627 7125

2. HAZARDS IDENTIFICATION

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

Aquatic Acute 2 H401 Toxic to aquatic life.

Signal Word Warning

Hazard Statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P273 Avoid release to the environment.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 2)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 RESIN 28gm

(Contd. of page 1)

P272	Contaminated work clothing should not be allowed out of the workplace.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water.
P391	Collect spillage.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national regulations.

3 . COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:		
25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	30 - 60%
7727-43-7	Sulfuric acid, barium salt (1:1)	10 - 30%
1317-65-3	Limestone ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	10 - 30%
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	1 - 5%
546-93-0	Carbonic acid, magnesium salt (1:1)	1 - 5%
7631-86-9	Silica	1 - 5%

4 . FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. It may be dangerous to the person giving aid to give mouth-to-mouth resuscitation. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, hold eyelids open and rinse with water for at least 15 minutes. Seek medical attention if symptoms occur.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Give a glass of water. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Seek immediate medical attention.

(Contd. on page 3)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 RESIN 28gm

(Contd. of page 2)

Symptoms Caused by Exposure:

Skin Contact: Causes skin irritation and redness. May cause an allergic skin reaction.

Eye Contact: Causes serious eye irritation, redness and watering.

5 . FIRE FIGHTING MEASURES**Suitable Extinguishing Media:** Use fire extinguishing methods suitable to surrounding conditions.**Specific Hazards Arising from the Chemical:**

Hazardous combustion products include oxides of carbon and sulphur, metal oxides and halogenated compounds.

Product does not sustain combustion.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 . ACCIDENTAL RELEASE MEASURES**Personal Precautions, Protective Equipment and Emergency Procedures:**

Wear approved dust/particulate filter respirator and full protective clothing. Evacuate all non-essential personnel from affected area. Do not breathe dust. Ensure adequate ventilation. Avoid generating dust.

Environmental Precautions: In the event of a major spill, prevent spillage from entering drains or water courses.**Methods and Materials for Containment and Cleaning Up:**

Stop leak if safe to do so, collect with a HEPA vacuum and place in a suitable container for subsequent disposal. Avoid generating dust. Do not dry sweep. Provide adequate ventilation.

7 . HANDLING AND STORAGE**Precautions for Safe Handling:**

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of dust.

Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Contaminated work clothing must not be allowed out of the workplace.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep in original container tightly closed. Do not store above 35 °C.

8 . EXPOSURE CONTROLS AND PERSONAL PROTECTION**Exposure Standards:****7727-43-7 Sulfuric acid, barium salt (1:1)**NES TWA: 10 mg/m³**1317-65-3 Limestone**WEL TWA: 10 mg/m³ (inhalable dust) 4 mg/m³ (respirable dust)**14807-96-6 Talc (Mg₃H₂(SiO₃)₄)**NES TWA: 2.5 mg/m³

(Contd. on page 4)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 RESIN 28gm

(Contd. of page 3)

546-93-0 Carbonic acid, magnesium salt (1:1)	
NES	TWA: 10 mg/m ³
7631-86-9 Silica	
NES	TWA: 2 mg/m ³

Engineering Controls:**Respiratory Protection:**

Where an inhalation risk exists, wear a Class P1 (particulate) respirator. At high dust levels, wear a powered air purifying respirator (PAPR) with Class P3 (Particulate) filter or an air-line respirator or a full-face Class P3 (particulate) respirator. See Australian/New Zealand Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Chemical resistant gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information.

When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against splashing materials or liquids. See Australian/New Zealand Standard AS/NZS 1337 for more information.

Eye and face protectors for protection against dust. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 . PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form: Solid
Colour: Metallic, grey
Odour: Ethereal

Odour Threshold: No information available

pH-Value: No information available

Melting point/Melting range: No information available

Initial Boiling Point/Boiling Range: No information available

Flash Point: > 93.3 °C

Flammability: Product does not sustain combustion.

Auto-ignition Temperature: No information available

Decomposition Temperature: No information available

Explosion Limits:

Lower: No information available

Upper: No information available

Vapour Pressure: Not applicable.

Relative Density: 1.866

Vapour Density: No information available

Evaporation Rate: No information available

Solubility in Water: No information available

(Contd. on page 5)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 RESIN 28gm

(Contd. of page 4)

Partition Coefficient (n-octanol/water): No information available

10 . STABILITY AND REACTIVITY

Possibility of Hazardous Reactions: No hazardous reactions will occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: No further relevant information available.

Incompatible Materials: No further relevant information available.

Hazardous Decomposition Products:

Oxides of carbon and sulphur, metal oxides and halogenated compounds.

11 . TOXICOLOGICAL INFORMATION

Toxicity:

LD ₅₀ /LC ₅₀ Values Relevant for Classification:		
1317-65-3 Limestone		
Oral	LD ₅₀	6450 mg/kg (rat)
7631-86-9 Silica		
Oral	LD ₅₀	10000 mg/kg (rat)
546-93-0 Carbonic acid, magnesium salt (1:1)		
Oral	LD ₅₀	8000 mg/kg (rat)

Acute Health Effects

Inhalation: May cause respiratory irritation.

Skin: Causes skin irritation and redness. May cause an allergic skin reaction.

Eye: Causes serious eye irritation, redness and watering.

Ingestion: No information available

Skin Corrosion / Irritation: Causes skin irritation.

Serious Eye Damage / Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitisation: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity:

Silica, amorphous and talc not containing asbestos or asbestiform fibres are classified by IARC as Group 3 - Not classifiable as to its carcinogenicity to humans.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Single Exposure: May cause respiratory irritation.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.

(Contd. on page 6)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 RESIN 28gm

(Contd. of page 5)

Chronic Health Effects:

Repeated or prolonged exposure may cause damage to the lungs, upper respiratory tract, skin and eyes. Once sensitised to the product allergic reactions may occur following even very low levels of exposure.

Existing Conditions Aggravated by Exposure: No information available

12 . ECOLOGICAL INFORMATION

Ecotoxicity:**Aquatic toxicity:**

Toxic to aquatic life with long lasting effects.

7727-43-7 Sulfuric acid, barium salt (1:1)

EC₅₀/48 h | 634 mg/L (crustacea)

7631-86-9 Silica

EC₅₀/72 h | 55.5 mg/L (algae)

Persistence and Degradability: No information available

Bioaccumulative Potential: The product has low potential for bioaccumulation.

Mobility in Soil: No information available

Other adverse effects: No information available

13 . DISPOSAL CONSIDERATIONS

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14 . TRANSPORT INFORMATION

UN Number

ADG

IMDG, IATA

Not regulated

UN3077

Proper Shipping Name

ADG

IMDG

Not regulated

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Phenol, 4.4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Phenol, 4.4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane)

IATA

Dangerous Goods Class

ADG Class:

IMDG Class:

Not regulated

9 Miscellaneous dangerous substances and articles.

Packing Group:

ADG

Not regulated

(Contd. on page 7)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 RESIN 28gm

(Contd. of page 6)

IMDG, IATA	III
Marine pollutant:	Yes Symbol (fish and tree)
EMS Number:	F-A,S-F
Hazchem Code:	2Z
Special Provisions:	179, 274, 331, 335, AU01
Limited Quantities:	5 kg
Packagings & IBCs - Packing Instruction:	P002, IBC08, LP02
Packagings & IBCs - Special Packing Provisions:	PP12, B3
Portable Tanks & Bulk Containers - Instructions:	T1, BK2
Portable Tanks & Bulk Containers - Special Provisions:	TP33

15 . REGULATORY INFORMATION

Australian Inventory of Chemical Substances:

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
7727-43-7	Sulfuric acid, barium salt (1:1)
1317-65-3	Limestone
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)
546-93-0	Carbonic acid, magnesium salt (1:1)
7631-86-9	Silica

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:

Not Scheduled.

None of the ingredients is listed.

16 . OTHER INFORMATION

Date of Preparation or Last Revision: 25.01.2021**Prepared by:** MSDS.COM.AU Pty Ltdwww.msds.com.au

Abbreviations and acronyms:

ADG: Australian Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC₅₀: Lethal concentration, 50 percentLD₅₀: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

(Contd. on page 8)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 06.05.2016

Revision: 25.01.2021

Product Name: DYNAGRIP EPOXY PASTE – 17002 RESIN 28gm

(Contd. of page 7)

Skin Sens. 1: Skin sensitisation, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Aquatic Acute 2: Hazardous to the aquatic environment, short-term (Acute). Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term (Chronic). Category 2

Disclaimer

This SDS is prepared in accord with the Safe Work Australia document “Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - December 2011”

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. AFC International Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.